



PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN COMPLIANCE WITH RULE 17.1(a) OR (b)

Patent Office Canberra

RECEIVED

06 SEP 2004

PCT

WIPO

I, LEANNE MYNOTT, MANAGER EXAMINATION SUPPORT AND SALES hereby certify that annexed is a true copy of the Provisional specification in connection with Application No. 2003903877 for a patent by BRYAN JAMES LARKIN as filed on 28 July 2003.



WITNESS my hand this Eleventh day of August 2004

LEANNE MYNOTT

MANAGER EXAMINATION SUPPORT

AND SALES

APPLICANT: BRYAN JAMES LARKIN 11 PRISTINE COURT STEPHENS OUEENSLAND 4226

AEROSOL SPRAY CAN WITH INTERNAL MAGNET DRIVEN IMPELLER

TECHNICAL FIELD

THIS INVENTION RELATES TO THE FIELD OF AEROSOL SPRAY CANS.

BACKGROUND ART

IT IS RECOGNISED THAT AEROSOLS THAT HAVE PAINT OR ADHESIVE INSIDE HAVE TO BE MIXED FOR A LONG TIME BY SHAKING THE CAN WHICH MOVES A BALL INSIDE TO MIX THE PROPELLANT AND LIQUID TO BE SPRAYED. WHEN SPRAYING PAINT AND ADHESIVE OR ANY OTHER LIQUID WHICH IS THICK LIKE FOAM YOU MUST STOP SPRAYING TO PREPARE THE JOB FOR A PERIOD AND THEN COMMENCE SPRAYING AGAIN BUT THE LIQUID HAS SETTLED TO THE BOTTOM OF THE AEOSOL AGAIN SO YOU HAVE TO START SHAKING THE CAN AGAIN TO MIX THE PROPELLANT AND LIQUID. A LOT OF THE TIME IS THEN SPENT TRYING TO CLEAN BLOCKED NOZZLES BECAUSE THE MIXTURE IS TOO THICK TO SPRAY.

DISCLOSURE OF INVENTION

THIS INVENTION IN ONE ASPECT RESIDES IN AN AEROSOL SPRAY CAN THAT HAS AN IMPELLER INSIDE WHICH HAS MAGNETS INSERTED INTO IT. UNDER THE CAN IS A FLYWHEEL WHICH ALSO HAS MAGNETS INSERTED INTO IT. THIS FLYWHEEL COULD THEN BE DRIVEN MANUALLY WITH A CRANK OR BY WINDING UP A SPRING AND RELEASING IT. THE CAN COULD ALSO BE MANUFACTURED TO FIT INTO A SEPERATE BASE UNIT WHICH HAS A BATTERY AND ELECTRIC MOTOR WHICH IS ACTIVATED BY THE CAN BEING INSERTED TRIGGERING A SWITCH TO START THE MOTOR WHICH WOULD DRIVE THE FLYWHEEL WHICH WOULD TURN THE IMPELLER AND MIX THE PROPELLANT. BY USING MAGNETS TO CONNECT THE FLYWHEEL AND THE IMPELLER THERE IS NO NEED FOR A DRIVE SHAFT TO ENTER THE CAN VIA A SEAL WHICH COULD LEAK UNDER HIGH PRESSURE.

BRIEF DESCRIPTION OF DRAWINGS

IN ORDER THAT THIS INVENTION MAY BE MORE EASILY UNDERSTOOD AND PUT INTO PRACTICAL EFFECT REFERENCE WILL BE MADE TO THE DRAWING ACCOMPANYING THIS DOCUMENT WHICH SHOW THE PREFFERED EMBODIMENT OF THE INVENTION, WHEREIN THE FIGURES SHOW THE UNIT HAVING A SEPERATE BASE UNIT WITH BATTERIES AND AN ELECTRIC MOTOR DRIVING THE FLYWHEEL AND IMPELLER.

IP Australia	Ď,
Documents received on:	Brisbane
2 8 JUL 2003	ane
Batch No:	





IT WILL OF COURSE BE REALISED THAT WHILST THE ABOVE HAS BEEN GIVEN BY WAY OF AN ILLUSTRATIVE EXAMPLE OF THIS INVENTION, ALL SUCH OTHER CHANGES OR MODIFICATIONS AND VARIATIONS HERETO, AS WOULD BE APPARENT TO PERSONS SKILLED IN THE ART, ARE DEEMED TO FALL WITHIN THE BROAD SCOPE AND AMBIT OF THIS INVENTION IS HEREIN SET FORTH.


DATED THIS STIT DAY OF SULG 2003

BY

BRYAN JAMES LARKIN







1/3 2/3

3/3

- 1 AEROSOL CAN
- 2 IMPELLER
- 3 DRIVEN MAGNETS
- 4- SHAFT
- 5 BASE
- 6 FLYWHEEL
- 7 DRIVE MAGNETS
- 8- MOTOR
- 9 SWITCH
- 10 BATTERIES

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

BLACK BORDERS
\square image cut off at top, bottom or sides
☐ FADED TEXT OR DRAWING
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
☐ SKEWED/SLANTED IMAGES
COLOR OR BLACK AND WHITE PHOTOGRAPHS
GRAY SCALE DOCUMENTS
LINES OR MARKS ON ORIGINAL DOCUMENT
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
Потить

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.